

BUSTER 150

≈ 74 m*

*Based on ANSI Beam FC1

≈ 25 h

SAFE

OSRAM
LEDs Included



BUSTER 150 MODES		
MODE	LUMENS	RUN TIME
High	≈ 150	≈ 3 h
Mid	≈ 75	≈ 7.5 h
Low	≈ 35	≈ 14.5 h
Night Flashing	≈ 100 / 40	≈ 5 h
Day Flashing	≈ 40	≈ 25 h



Ø 22 - 35mm



NL 360° verstelbare siliconen houder
FR Attache souple en silicone, ajustable à 360°, ø / fixation à glissière
IT Supporto in silicone regolabile a 360°. Quick Release incl.
ES Soporte ajustable 360°, de rápida liberación

NL USB-C oplaadfunctie
FR Recharge par USB-C
IT Funzione di carica USB-C
ES Carga por USB-C

NL Zijdelingse zichtbaarheid
FR Visibilité latérale
IT Visibilità laterale
ES Visibilidad lateral

A
NL 5 licht-modi met 5 voorinstelbare „licht-profielen“ en licht-modus geheugenfunctie
FR 5 Modes d'éclairage avec 5 Profils pré-réglés & Mémoire du mode
IT 5 modalità con 5 profili preinstallati + modalità memoria
ES 5 Modos con 5 perfiles preajustados y memoria del último modo utilizado

Contents



SILICONE BRACKET



USB-C-CABLE



ACTION CAMERA ADAPTER



BUSTER
150 LUMENS

SIGMA®

BUSTER
150 LUMENS

POWER ON
EXPERIENCE THE
LIGHT OF THE BUSTER



BUSTER 150 LUMENS

SIGMA-ELEKTRO GmbH Dr.-Julius-Leber-Straße 15 87433 Neustadt/Wstr. Germany service@sigma.bike

sigma.bike




MIX Board | Supporting responsible forestry
FSC® C103634

Manufactured in China



ART-NR. 19150



UK FC CE

179151/4