

# BUSTER 400

≤ 120 m<sup>2</sup>  
\*Based ANSI Beam FC1

≤ 25 h

SAFE

OSRAM  
LEDs Included



A  
Ø 22 - 35mm



NL USB-C oplaadfunctie  
FR Recharge par USB-C  
IT Funzione di carica USB-C  
ES Carga por USB-C



NL Zijdelingse zichtbaarheid  
FR Visibilité latérale  
IT Visibilità laterale  
ES Visibilidad lateral



BUSTER 400 MODES		
MODE	LUMENS	RUN TIME
High	≈ 400	≈ 2 h
Mid	≈ 200	≈ 4 h
Low	≈ 100	≈ 9 h
Night Flashing	≈ 300 / 100	≈ 5 h
Day Flashing	≈ 100	≈ 25 h

**A**  
NL 360° verstelbare siliconen houder  
FR Attache souple en silicone, ajustable à 360°, w/ fixation à glissière  
IT Supporto in silicone regolabile a 360°. Quick Release incl.  
ES Soporte ajustable 360°, de rápida liberación

**B**  
NL 5 licht-modi met 5 voorafgestelde „licht-profielen“ en licht-modus geheugenfunctie  
FR 5 Modes d'éclairage avec 5 Profils pré-réglés & Mémoire du mode  
IT 5 modalità con 5 profili preinstallati + modalità memoria  
ES 5 Modos con 5 perfiles preajustados y memoria del último modo utilizado

**C**  
NL 6-traps accu-indicator  
FR Indicateur de batterie à 6 niveaux  
IT Visualizzazione batteria a 6 livelli  
ES Indicador de batería de 6 niveles

## Contents



SILICONE BRACKET



USB-C-CABLE



ACTION CAMERA ADAPTER

# SIGMA

# BUSTER 400 LUMENS

# BUSTER 400 LUMENS

POWER ON  
EXPERIENCE THE  
LIGHT OF THE BUSTER



# BUSTER 400 LUMENS

SIGMA-ELEKTRO GmbH Dr.-Julius-Leber-Straße 15 87433 Neustadt/Wstr. Germany service@sigma.bike

sigma.bike



Manufactured in China



UK

FC

CE

UK

179601/4