

# BUSTER 800

≤ 170 m\*

\*Based ANSI Beam FC1

≈ 30 h

SAFE

CREE LEDs



A Ø 22 - 35mm



B

C

BUSTER 800 MODES			
MODE	INDICATOR	LUMENS	RUN TIME
High		≈ 800	≈ 2 h
Mid		≈ 400	≈ 3 h
Low		≈ 150	≈ 9 h
Night Flashing		≈ 600 / 200	≈ 5 h
Day Flashing		≈ 200	≈ 30 h



NL USB-C oplaadfunctie  
FR Recharge par USB-C  
IT Funzione di carica USB-C  
ES Carga por USB-C



NL Zijdelingse zichtbaarheid  
FR Visibilité latérale  
IT Visibilità laterale  
ES Visibilidad lateral

A

NL 3D-instelbare houder incl. snelspanner  
FR Support ajustable 3D avec serrage rapide  
IT Supporto 3D regolabile. Sgancio rapido incl.  
ES Soporte ajustable en 3D incl. cierre rápido

B

NL 5 Lichtmodus indicator met 5 voorinstelbare „licht-profielen“ en licht-modus geheugenfunctie  
FR Témoin du mode éclairage à 5 niveaux 5 Profils pré-réglés & Mémoire du mode  
IT Visualizzazione di 5 modalità sul display con 5 profili preinstallati + modalità memoria  
ES Indicador de 5 modos con 5 perfiles preajustados y memoria del último modo utilizado

C

NL 6-traps accu-indicator  
FR Indicateur de batterie à 6 niveaux  
IT Visualizzazione batteria a 6 livelli  
ES Indicador de batería de 6 niveles

SIGMA-ELEKTRO GmbH Dr.-Julius-Leber-Straße 15 87433 Neustadt/Wstr. Germany service@sigma.bike

sigma.bike

Manufactured in China



ART-NR. 19800

## Contents



SCREW-BRACKET MOUNT



3D RUBBER PAD



USB-C CABLE



ACTION CAMERA ADAPTER



LONG SCREW




# BUSTER 800 LUMENS

# SIGMA

# BUSTER 800 LUMENS

# BUSTER 800 LUMENS

POWER ON  
EXPERIENCE THE  
LIGHT OF THE BUSTER



UK

FC

CE

UK

179801/4